

Impact-R 4100




Features

The Impact-R 4100 series computers are powered by Intel® based commercial motherboards, delivering a compact and flexible computer platform.

- Intel® Comet Lake CPU architecture
- DDR4 Memory up to 128GB
- Supports 3 native displays simultaneously

Our production processes are controlled under ISO 9001 and every system undergoes a full diagnostic burn-in prior to shipment.

Dimensions



Configuration shown is for illustration purposes only

Impact-R 4100

The information is believed to be accurate. However Amplicon Liveline Limited accepts no responsibility for any problems caused by errors and omissions. Specifications are subject to change without notice.

Specifications

| | | | |
|------------------------|---|---|--|
| Hardware Specification | CPU: Intel® LGA1200 10th Generation Core™ i9/i7/i5/i3 and Xeon Chipset: Intel® V480E Memory: 4 x DIMM - max 128GB DDR4 2933MHz non-ECC/LAN: Intel® I211AT/I219LM GbE | Environmental operation | Acoustic noise: Approximately 49dB(A) sound pressure at 23°C (typical) Temperature: 5 to 60°C (tested for extended operation up to 50°C) Humidity: 5 to 90% at 25°C non-condensing |
| BIOS | Insyde | Optional Breakout Interfaces (Will use 1 slot per breakout) | 1 x RS-232/422/485 (RS-232 w/ power) 4 x RS-232 2 x USB 3.2 Gen 2 2 x USB 2.0 1 x USB 2.0 Vertical Type A 1 x Front Audio Header 1 x S/PDIF SATA 1 x PS/2 (mini-DIN-6) LPC 1 x LPC (supports LPC EXT-RS232/RS485 module) DIO 1 x 16-bit DIO |
| Display | 1 x VGA, resolution up to 1920x1200 @ 60Hz 1 x DP++, resolution up to 4096x2160 @ 60Hz 1 x HDMI 1.4b, resolution up to 4096x2160 @ 24Hz | Mechanical | Design: EIA RS-310C 19" Rackmount Standard Construction: 1.2mm SECC Zinc-Coated Steel Security: Lockable front door Colour: Black (custom colours available for large orders) Dimensions: 483 x 177 x 573mm (19.0" x 7.0" x 22.6") Packaging Size: 590mm x 331mm x 750mm (23.2" x 13.0" x 29.5") Cooling: 3x 120mm ball bearing fan Air filter: removable (washable) Gross Weight: approximately 22 kg |
| Storage | Total Drive capacity: 6 x 5.25", 1 x 3.5" external, 1 x 3.5" internal RAID: 0, 1, 5, 10 Dual M.2 also available | Reliability | System MTBF: Critical components failure >45,000 hrs @ 25°C (we can provide information for specific configurations). Full burn-in diagnostic run on every system. |
| System Expansion | 2 x PCIe x16 (Gen 3) (1 x16 signal or 2 x8 signal) 3 x PCIe x4 (Gen 3) (2 x4 signal and 1 x1 signal) 2 x PCI 2 x M.2 M key PCIe 3.0 x 4 NVME | Certification | CE/UKCA |
| System Architecture | Intel® Based Industrial motherboard | | |
| Supported O/S | Windows 10/Linux | | |
| External Interfaces | Front: 2 x USB 2.0/1.1 On/Off Switch, Reset Pwr/HDD LEDs Rear: 2 x GbE (RJ-45) 1 x RS-232/422/485 (RS-232 w/ power) (DB-9) 2 x USB 3.2 Gen2 2 x USB 3.2 Gen1 4 x USB 2.0 1 x VGA, 1 x DP++, 1 x HDMI 1 x Line-out, 1 x Mic-in, | | |
| Environmental storage | Temperature: -20 to 65°C Humidity: 5 to 90% at 25°C non-condensing | | |